

PRODUCT  
SPECIFICATION

 **TEREX**<sup>®</sup>

 **ECOTEC**

# TDS 820

SLOW SPEED SHREDDER



# AGGRESSIVE SLOW SPEED SHREDDER

The TDS 820 is an aggressive slow speed shredder suitable for all types of material. Customisable shredding programs allow operators to configure the machine to their specific requirements, reducing wrappage and maximising production.



# TDS 820

Independent shredding shafts allow for maximum application flexibility.



Key features include the hydrostatic drive offering better protection against contamination and allowing for bi-directional shredding. The double shaft shredder has 2m long shafts with a fully welded tooth configuration, impressive throughput and excellent reduction.

The independent gearboxes enable each shaft to be run separately helping to reduce wrappage and improve the shredding of material.

Additional features include the tipping feeder which increases the feed area. Hopper extensions provide increased capacity in bulky applications.

The TDS 820 is powered by the following engines dependent on geographic area and emission regulations; Scania DC13 331kW (440HP) Stage V for EU, Scania DC13 331kW (440HP) Tier 4 Final for the USA and Scania DC13 371kW (497HP) Stage IIIA Constant Speed for ROW.

The machine is manoeuvred via a robust tracked undercarriage making it a great solution for difficult terrain.

# KEY FEATURES



A powerful Scania engine with a low operating speed combined with an efficient hydrostatic drive creates a very responsive shredding action with protection against unshreddable contaminants



User friendly colour display offering simple operation and diagnostics  
 Customisable shredding programs allow operators to tailor the machine for specific applications



Robust German designed shredding chamber  
 Independently driven shafts give excellent shredding performance in even the most challenging of applications



Shaft cutting elements are a fully welded structure with hard-faced edges giving ultimate strength in difficult applications

Excellent service access reduces operator downtime



A separate transfer conveyor with a high specification belt ensures material is effectively removed from below the shredding chamber

# TECHNICAL DATA



TRANSPORT DIMENSIONS	POWERUNIT	TRACKED UNDERCARRIAGE
Length: 9100mm (29' 10")	Engine:	Bolt on tracks
Width: 2500mm (8' 2")	<ul style="list-style-type: none"> <li>Scania DC13 331kW (440HP) Stage V (EU)</li> <li>Scania DC13 331kW (440HP) Tier 4 Final (USA)</li> <li>Scania DC13 371kW (497HP) Stage IIIA Constant Speed (ROW)</li> </ul>	500mm (20") shoe
Height: 3200mm (10' 6")	CleanFix variable pitch cooling fan	2920mm (9' 7") sprocket centres
Weight: 27,500kg (60,627lbs) (dependent on options)	Shredder drive: Twin Hydrostatic (independent shaft drive)	OPTIONS
	Fuel capacity: 500l	Overband Magnet
	CAN BUS control system with user friendly colour display offering simple operation and diagnostics	Various Shaft/Breaker Bar Configurations
		Plant Autolube (Excluding Shredder Shafts)
		Extended Discharge Conveyor
		Hydraulic Raise / Lower Overband Magnet
		Hydraulic Folding Hopper Extensions
		Chamber Camera & Monitor
WORKING DIMENSIONS	TRANSFER CONVEYOR	
Length: 11700mm (38' 5") (product belt @ 35°)	Width: 1300mm (4' 3")	
Width: 2500mm (8' 2")	Length: 2450mm (8' 0")	
Feed Height: 3200mm (10' 6")	Max. belt speed: 130m/min (426' 6"/min)	
Discharge Height: 3900mm (12' 10") - 1700mm (5' 7")	PRODUCT CONVEYOR	
	Width: 1400mm (4' 7")	
	Length: 5500mm (18")	
	Max. belt speed: 130m/min (426' 6"/min)	
SHREDDING UNIT		
Type of shredder: Twin shaft slow speed		
Shaft Length: 2000mm		
Shaft diameter: 700mm		
Torque per shaft: 100 000Nm		
Tilting feeder capacity: 7m <sup>3</sup>		
Autolube for shredder shaft bearing		

Specification subject to change without notice

# CUSTOMER SUPPORT

With you every step of the way

We work with our customers to understand their equipment needs to select the product most suited to their business requirements. Terex Ecotec customer support incorporates a range of services including parts, technical support, warranty and financial services.



## The Right Part at the Right Time

Terex Ecotec has a full inventory of genuine Terex parts through our global support locations and dealer network. We are committed to getting the right parts delivered at the right time. Using genuine Terex parts ensures optimum performance and reliability.



## Warranty Delivering on our promise so you can keep yours

Terex Ecotec warrants its new equipment to be free of defects in material or manufacture for a specified period from the date the equipment is first used.



## Expert technical support

Terex Ecotec provide highly qualified service personnel to ensure that we have the ability to provide technical support when our customers need it. This support is provided in conjunction with our dealer network. We ensure our customers are supported throughout the lifecycle of their machine.



## Terex Financial Services Financing that works for you

Terex Ecotec are able to offer finance solutions to our customers. Our team of finance professionals know the importance of working closely with customers to understand their unique business challenges as well as their financial goals and requirements. Obtaining financing is often a time-consuming task, so we work hard to provide a reliable, flexible and responsive service.



Delivering On Our Promises,  
So You Can Keep Yours.



## CAMPSIE

20 Keans Hill Road  
Campsie Industrial Estate  
BT47 3YT, Northern Ireland

Tel: +44 (0) 28 7122 3110

## DUNGANNON

32 Farlough Road  
Dungannon, Co. Tyrone  
BT71 4DT, Northern Ireland

Tel: +44 (0) 28 8771 8500

---

Dealer Stamp:

## NEWTON

22 Whittier Street  
Newton, New Hampshire  
USA, 03858

Tel: +1 (603) 382 0556

---

February 2021. The material in this document is for information only and is subject to change without notice. Terex Ecotec assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Any product performance figures given in this brochure are for guidance purposes only. This information does not constitute an expressed or implied warranty or guarantee, but shows text examples provided. These results will vary depending on product settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only. Some or all of the machines in the illustrations may be fitted with optional extra. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries © 2021 Terex Corporation.